











PRODUCT CATALOGUE

[COMMERCIAL VEHICLES]

MUDGUARDS, SPRAY-SUPPRESSION AND MUDFLAPS INSTALLATION PARTS TOOLBOXES AERO PANELS

AGRI & INDUSTRIAL EQUIPMENT

OFF-RD FRONT MUDGUARDS OFF-RD SHORT MUDGUARDS OFF-RD LONG MUDGUARDS

[CONTRACT MANUFACTURING]

[CONTENTS]



	MUDGUARDS,	
	SPRAY-SUPPRESSION	
	AND MUDFLAPS	
1.1	WHITE LINE	12
1.2	WHITE LINE SUPRA	14
1.3	WHITE LINE 1/4	16
1.4	WHITE LINE 1/4 SUPRA	18
1.5	BLACK LINE	20
1.6	STEERING AXLE MUDGUARDS	2
1.7	TANDEM / TRIDEM MUDGUARDS	2
1.8	WHITE LINE 3-PIECE MUDGUARDS	28
1.9	COLOUR LINE	30
1.10	FLAT TOP	32
1.11	SPAT	34
1.12	VALANCE	3!
1.13	MUDFLAPS	30





2	INSTALLATION PARTS	38
2.1	BRACKETS	40
2.2	TUBE STAYS AND BUSHINGS	48

3	TOOLBOXES52	
4 4.1 4.2 4.3 4.4	AERO PANELS	
5.1 5.2 5.3 5.4	AGRI & INDUSTRIAL EQUIPMENT	
6.1 6.2 6.3 6.4	CONTRACT MANUFACTURING 72 SHEET PRODUCTS 72 VACUUM-FORMING 73 ASSEMBLY 73 DESIGN 73-	



[COMMERCIAL VEHICLES]

1 MUDGUARDS, SPRAY-SUPPRESSION AND MUDFLAPS

PARLOK - THE COMPANY

Oy Parlok Ab is one of the world's leading manufacturers of mudguards and spray-suppression systems. We also manufacture a wide range of other plastic products. Our mission is to improve road safety with cost-effective solutions.

We offer a wide variety of mudguards in different forms and sizes, with or without anti-spray, used in commercial vehicles. They are all made of the very durable PE-HD (high-density polyethylene) in our own unique production process providing a well-finished appearance.

With efficient production machinery and in strong investments in product development we develop our basic products constantly and create new cost-effective customer solutions.



Safe, durable premium quality

The Parlok products are certified and represent outstanding quality. The material PE-HD is extremely wear-resistant. In addition to quality, durability and safety, we focus strongly on environmental friendliness and energy efficiency. Our operations fulfill the strict requirements of the ISO 9001 and ISO 14001 standards. We constantly develop our operations in order to meet the demands of customers and the environment even better.

Customised and reliable service

Our aim is to establish long-term customer relationships based on a high degree of customer satisfaction. In addition to our broad product range of standard products we customise products according to customers' preferences. We have a global cooperation network and customers are always served by a country-specific dealer.

- + Recyclable raw material PE-HD (high-density polyethylene)
- + Large range of usage temperature from -50°C to +80°C
- + Good chemical resistance
- + Very light weight
- + Easy to install
- + Integrated spray-suppression available
- + Large selection of different sizes
- + High impact resistance
- + Attractive design




We produce virtually no waste nor emissions and our products are completely recyclable.

REGULATION (EU)-SPRAY-SUPPRESSION SYSTEMS


EC COUNCIL DIRECTIVES

References to the regulations (EU) 2019/2144; 6.7.2022 and (EU) 2021/535; 31.3.2021 on the approximation of laws of the Member States relating to the spray-suppression system of certain categories of motor vehicles and their trailers.



WHICH VEHICLES

All tractors and rigid vehicles usable for carriage of goods having a maximum mass exceeding 7,5 tonnes and all trailers with a maximum weight exceeding 3,5 tonnes: must be constructed and/or fitted with spraysuppression systems or devices (certain vehicles as unbodied vehicles, "off road" vehicles etc. are excepted).





SYSTEM OR DEVICE

Spray-suppression system reduces the pulverization of water thrown by tyres from wet road. The spray suppression system can be made up of a mudguard part and a rain flap part equipped with a spray-suppression device.

Spray-suppression device is a component forming part of the mudguard and/or rain flap and it absorbs the energy of water spray.

MEASUREMENTS OF THE SYSTEM


The width of the mudguard part and the flap part must cover the entire width of the tyre specified by the tyre manufacturer.


The front edge must extend no more than 45° above the axle line with non-steered wheels.

Depth of the outer valance must extend not less than 45 mm at all points behind a vertical line passing through the center of the wheel.

Spray suppression device

The back side of the rear part of the system must be fitted with a spray-reduction device. This material must cover the inside of the system up to a height determined by a straight line running from the centre of the wheel and forming an angel of at least 30° with the horizontal. The lower rear edge of the spray- suppression system must not be more than 200 mm, in special cases 300 mm, from the ground.





TYRE		DUAL	MAX.	WHITE	LINE	FLAT	ТОР	WHITE LIN	IE SUPRA
DIMENSION	WIDTH	SPACING	DIAM.	TWIN	SINGLE	TWIN	SINGLE	TWIN	SINGLE
8.25 R 15	237	267	830	101299	<u> </u>	100248		101990	
10.00 R 15	283	308	942	101110				104626	
7.00 R 16	204	230	795	101424		100248	100287		
7.50 R 16	216	240	814	101350		100248		101936	
8.25 R 16	237	264	874	101299		100248		101990	
9.00 R 16	253	274	927	101299		100256		101990	
255/100 R 16	262	282	936	101222		100256		102036	
305/95 R 16	300	335	1010	100865	404220			102240	404770
325/85 R 16	341	257	980	101200	101320	100256		101990	101779
8.25 R 17 205/75 R 17,5	237 213	257 231	900 765	101299 101350		100256 100271	100287	101990	
215/75 R 17,5	213	260	703	101350		100271	100287	101936	
225/75 R 17,5	237	266	797	101289		100246	100287	104648	
235/75 R 17,5	245	282	811	101289		100256	100207	104648	
245/75 R 17,5	260	290	827	101289		100256		104648	
225/70 R 17,5	235	263	773	101289		100248	100287	104648	
245/70 R 17,5	260	290	803	101289		100256		104648	
265/70 R 17,5	275	298	831	101222				102036	
205/65 R 17,5	214	234	721	101350		100271	100287	101936	
355/45 R 17,5	368		777		101320				101779
8 R 17,5	214	234	794	101350		100248		101936	
8.5 R 17,5	221	236	813	101350		100248		101936	
9 R 17,5	237	260	831	101350		100248		101936	
9.5 R 17,5	247	272	854	101299		100256		101990	
10 R 17,5	262	282	870	101222		100256		102036	
11 R 17,5	287	318	914	101110		400056		104626	
245/70 R 19,5	260	288	853	101299		100256		101990	
265/70 R 19,5 285/70 R 19,5	275 297	309 332	881 911	101126 101110				102086 104626	
305/70 R 19,5	320	354	941	100857				104627	
315/70 R 19,5	328	362	937	100857				104647	
245/65 R 19,5	248	280	814	101289				104648	
385/65 R 19,5	405		1020		101320				101779
445/65 R 19,5	477		1097		101378				101897
255/60 R 19,5	260	290	813	101215				102021	
425/55 R 19,5	442		981		101378				101897
385/55 R 19,5	400		936		101320				101779
265/55 R 19,5	265	295	799	101215				102021	
435/50 R 19,5	460		949		101378				101897
445/45 R 19,5	458		910		101378				101897
7 R 19,5	191	209	809	101424		100248			
8 R 19,5	214	229	867	101414		100248		101941	
9 R 19,5	237	260	906	101299		100256		101990	
9.5 R 19,5 10 R 19,5	247 262	274 292	926 949	101299 101167		100256		101990 104627	
11 R 19,5	287	317	984	101110				104627	
12 R 19,5	309	341	1023	100865	101320			102240	101779
15 R 19,5	399	311	998	100003	101320			1022 10	101779
16.5 R 19,5	438		1063		101454				101870
18 R 19,5	471		1100		101358				101952
19.5 R 19,5	495		1134		101358				101952
6.50 R 20	186	216	871	101414		100248		101941	
7.00 R 20	204	222	904	101414		100256		101941	
7.50 R 20	216	243	941	101378		100256		101897	
8.25 R 20	237	273	976	101311		100256			
9.00 R 20	266	296	1033	101137				102079	
10.00 R 20	283	319	1068	101137				102079	
11.00 R 20	295	339	1099	101052	40			102165	4645=-
12.00 R 20	319	358	1140	104449	101570			104623	101856
13.00 R 20	346		1196		101435				101882
14.00 R 20	377		1260						
385/90 R 20 225/90 R 20	398 240	276	1270 926	101299		100256		101990	
365/85 R 20	382	270	1152	101233	101570	100230		101330	101856
395/85 R 20	405		1206		101570				101856
12/80 R 20	314	349	1023	100865	101616			102240	101030
00 20	5.1	5.5	. 0_3	. 30003				. 5 10	13

				WHITE	LINE	FLAT TOF		WHITE LIN	E CLIDDA
TYRE DIMENSION	WIDTH	DUAL SPACING	MAX. DIAM.	TWIN	SINGLE		INGLE	TWIN	SINGLE
13/80 R 20	336		1064		101616				101743
14/80 R 20	361		1107		101616				101743
14.75/80 R 20	381		1142		101435				101882
15.5/80 R 20	396		1177		101570				101856
335/80 R 20	350		1066		101616				101743
365/80 R 20	382		1116		101479				101813
475/80 R 20	498		1298						
475/60 R 20	475		1078		101358				101952
12/80 R 22,5	320	344	1064	100865	101616			102240	101743
385/95 R 22,5	398		1270		101442				
375/90 R 22,5	387		1247		101442				
275/80 R 22,5	290	324	1030	101052				102165	
295/80 R 22,5	313	348	1062	100865				102240	
315/80 R 22,5	328	363	1096	104449	101616			104623	101743
215/75 R 22,5	211	246	894	101414		100248		101941	
295/75 R 22,5	313	348	1032	100865				102240	
315/75 R 22,5	328	360	1063	100991	101616			102305	101743
345/75 R 22,5	365		1111		101616				101743
350/75 R 22,5	364		1097		101616				101743
445/75 R 22,5	462		1266		101442				
255/70 R 22,5	268	297	944	101167				104627	
275/70 R 22,5	290	322	973	101110				104626	
295/70 R 22,5	313	330	1005	100865				102240	
305/70 R 22,5	320	349	1018	100865				102240	
315/70 R 22,5	328	360	1032	100991				102305	
365/70 R 22,5	380		1104		101616				101743
385/65 R 22,5	408		1092		101479				101813
425/65 R 22,5	452		1146		101435				101882
445/65 R 22,5	477		1174		101358				101952
265/60 R 22,5	275	300	890	101222				102036	
285/60 R 22,5	299	327	928	101110				104626	
295/60 R 22,5	307	333	940	101047				104625	
305/60 R 22,5	312	348	952	100857				104647	
315/60 R 22,5	319	360	966	100857	101320			104647	101779
385/55 R 22,5	401		1012		101616				101743
455/55 R 22,5	470		1092		101358				101952
355/50 R 22,5	375		942		101320				101779
445/50 R 22,5	463		1036		101378				101897
415/45 R 22,5	433		960		101378				101897
435/45 R 22,5	457		980		101378				101897
455/45 R 22,5	461		998		101378				101897
495/45 R 22,5	519		1036		101311				101995
445/40 R 22,5	453		936		101378				101897
455/40 R 22,5	453		936		101378				101897
8 R 22,5	214	247	947	101378		100256		101897	4040==
9 R 22,5	237	260	982	101311		100256		102070	101995
10 R 22,5	262	286	1033	101137				102079	
11 R 22,5	287	318	1064	101052				102165	
12 R 22,5	309	342	1099	100865				102240	
13 R 22,5	328	360	1141	104449	101470			104623	101013
15 R 22,5	399		1089		101479				101813
16.5 R 22,5	438		1139		101435				101882
18 R 22,5	471	257	1176	101200	101358	100356		101000	101952
9/70 R 22,5	236	257	901	101299		100256		101990	
10/70 R 22,5	262	286	938	101167		100256		104627	
11/70 R 22,5	279	322	973	101110				104626	
12/70 R 22,5	320	346	1018	100865	101616			102240	101743
13/70 R 22,5	340	242	1047	100024	101616			102200	101743
11.00 R 24	295	342	1199	100924				102289	
12.00 R 24	319	350	1244	104449	101425			104623	101000
14/80 R 24,5	361	245	1209	100057	101435			102206	101882
295/80 R 24,5	313	345	1112	100957				102206	
285/75 R 24,5	295	335	1050	101052				102165	
305/75 R 24,5	320	350	1098	100865				102240	
315/75 R 24,5	328	360	1112	104449				104623	

1.1 WHITE LINE™



The original Parlok White Line™ mudguard. Made of PE-HD (high density polyethylene) with a large range of usage temperature and excellent chemical resistance. Strong against wear & tear and light in weight. A wide range of lengths and widths can be made to various requirements.

WITH S42 & P42 BRACKETS




Original Parlok White Line™ with adjustable brackets. The range of adjustment 86 mm for P42 and 65 mm for S42 as well as the option to customise the bracket position offer an unlimited range to fit the mudguard on vehicle. A very strong combination for your mudguard solution with extremely easy installation. Just lift on tube stays and tighten the four nuts.

WHITE LINE	WITH S42	WITH P42	В	L	R	s	н	B1	L1
104449	104723	104722	720	2090	690	1380	650	450	920
100991	103186	100996	720	1900	630	1260	590	450	930
100924	100936	100931	680	2175	690	1380	690	350	920
104665	105089	105088	680	1975	630	1260	630	350	920
100865	103366	100893	680	1900	630	1260	590	350	920
100857	103365	103221	680	1800	580	1160	570	350	850
100854	103364	103220	680	1650	580	1150	495	350	850
100957	103367	100965	670	2090	670	1340	660	350	980
104466	104725	104724	650	1975	630	1260	630	350	920
101052	103185	101062	650	1900	630	1260	590	350	920
101047	103371	101049	650	1800	580	1160	570	350	850
101043	103370	103222	650	1650	580	1150	495	350	850
101110	101121	101118	630	1850	580	1160	595	335	850
101087	103374	101105	630	1650	580	1150	495	335	850
101126	103375	103223	630	1630	530	1060	515	335	770
101137	103376	101139	610	1930	640	1280	600	335	940
101167	101171	101170	600	1850	580	1160	595	335	850
101222	103380	101247	595	1700	550	1100	535	335	800
101215	103379	101219	595	1570	500	1000	500	335	730
101311	103383	101312	550	1900	605	1210	605	225	800
101299	101296	101303	550	1700	550	1100	535	225	800
101289	104695	104694	550	1600	500	1000	515	225	730
101286	104727	104726	550	1500	500	1000	465	225	730
101358	103386	101362	500	2140	685	1370	680	225	1000
101422	103389	103229	500	1900	605	1210	605	225	730
101414	103388	101420	500	1700	550	1100	535	225	730
101350	103384	103227	500	1600	500	1000	515	225	730
101378	103387	101397	480	1800	580	1160	570	225	850
101442	103391	103230	455	2290	730	1470	725	225	1000
101435	101439	101438	455	2090	685	1370	655	225	1000
101424	103390	101427	455	1600	510	1020	510	150	710
101463	103394	101465	450	2100	670	1340	670	225	950
101454	103393	101456	450	1900	650	1290	580	225	950
101453	103392	103231	450	1400	450	840	450	150	620
101449	104728	101452	450	1300	420	840	410	150	620
101570	103395	101578	430	2175	690	1380	690	150	950
101540	104730	104729	430	2050	650	1300	655	150	950
101479	101508	101497	430	1900	650	1290	580	150	950
101661	103397	103232	415	1420	450	900	455	150	620
101616	103396	101632	405	1900	635	1265	595	150	930
101320	101337	101335	405	1800	580	1160	570	150	850

1.2 WHITE LINE™ SUPRA





The original Parlok White Line™ mudguard with integrated spray-suppression. Made of PE-HD (high density polyethylene) with excellent temperature and chemical resistance. Strong against wear & tear and light in weight. A wide range of lengths and widths to various requirements. Logo print to mudflap available.

Parlok Supra™ integrated spray-suppression system meets the requirements of regulations (EU) 2019/2144; 6.7.2022 and (EU) 2021/535; 31.3.2021 related to the spray-suppression system of certain categories of motor vehicles and their trailers.


Parlok Supra spray-suppression system improves road safety by reducing 80% of the water spray generated at the tyre–road interface on wet surfaces, redirecting the water back onto the road. The Supra material is available either factory-integrated into the mudguard or as a separate component for retrofitting.

Homologation Number for Parlok WL Supra integrated spray-suppression material is e1*2021/535/8*2021/535*00039*00. Approval mark on the product: A e1 00 00039.

For more information about the regulations, see pages 8-9.

WITH S42 & P42 BRACKETS






The adjustable brackets are delivered integrated with Parlok White Line™ and Supra™ mudguards. This is a durable solution that enables customer-specific mounting solutions with a wide adjustment range (86 mm for P42 and 65 mm for S42) as well as easy installation.

WL SUPRA	WITH S42	WITH P42	В	L	R	s	н	F	B1	L1
104623	104732	104731	720	2490	690	1380	1050	400	450	920
102305	103352	102307	720	2300	630	1260	990	400	450	920
102289	103351	102292	680	2575	690	1380	1095	400	350	920
104708	104559	102298	680	2375	630	1260	1030	400	350	920
102240	103350	102267	680	2300	630	1260	990	400	350	920
104647	104734	104733	680	2100	580	1160	870	300	350	850
102230	103349	102224	680	2050	580	1150	895	400	350	850
102206	103348	102210	670	2490	670	1340	1060	400	350	980
104624	104735	102181	650	2375	630	1260	1030	400	350	920
102165	103346	102170	650	2300	630	1260	990	400	350	920
104625	104558	104736	650	2100	580	1160	870	300	350	850
102151	103345	102156	650	2050	580	1150	895	400	335	850
104626	104738	104737	630	2150	580	1160	895	300	335	850
102104	102127	102119	630	2050	580	1150	895	400	335	850
102086	103344	102095	630	1930	530	1060	815	300	335	770
102079	103343	102080	610	2330	640	1280	1020	400	335	940
104627	104740	104739	600	2150	580	1160	870	300	335	850
102036	102063	102058	595	2000	550	1100	835	300	335	800
102021	103340	102026	595	1870	500	1000	800	300	335	730
101990	103337	101993	550	2000	550	1100	835	300	225	800
104648	104397	105090	550	1900	500	1000	815	300	225	730
101967	103335	101971	550	1800	500	1000	765	300	225	730
101952	103334	103204	500	2540	685	1370	1080	400	225	1000
101941	103333	101947	500	2000	550	1100	835	300	225	800
101936	104741	101937	500	1900	500	1000	815	300	225	730
104628	104743	104742	500	1800	500	1000	765	300	225	730
101897	103330	101915	480	2100	580	1160	870	300	225	850
101882	103328	101884	455	2490	685	1370	1055	400	225	1000
101887	103329	101888	450	2500	670	1340	1070	400	225	950
101870	103327	101875	450	2300	650	1290	980	400	225	950
101856	103326	101857	430	2575	690	1380	1090	400	150	950
104629	104745	104744	430	2450	650	1300	1055	400	150	950
101813	101836	101828	430	2300	650	1290	980	400	150	900
101743	103322	101762	405	2300	635	1265	995	400	150	930
101779	103325	101795	405	2100	580	1160	870	300	150	850

- + Supra spray-suppression has a selfcleaning construction
- + It is light in weight and is fitted on the mudguard with a bolt or a rivet joint
- + Material is PE-HD (high density polyethylene)
- + Supra is available also as a separate anti-spray mat for special constructions. See page 36.

1.3 WHITE LINE 1/4






Parlok White Line™ 1/4 mudguard is a cost effective solution for installations where a full-length mudguard can't be fitted. Available also with integrated Supra spray-suppression.

WITH S42 & P42 BRACKETS





White Line™ 1/4 mudguard for where the space doesn't allow a full-length mudguard. With the adjustable brackets the installation is very easy. S42 and P42 brackets secure the quarter mudguard tightly on the tube stay preventing it from spinning. The range of adjustment is 86 mm for P42 and 65 mm for S42.


WL 1⁄4	WITH S42	WITH P42	В	L	R	s	н	В1	L1
100986	103398	100987	720	700	630	345	565	450	350
100843	103401	100846	680	700	630	345	565	350	350
101017	101020	101019	650	650	630	305	540	350	325
101156	101157	103233	600	650	580	325	520	335	325
101273	101275	101274	550	650	550	340	505	225	325
101315	103400	101316	500	650	500	360	480	225	325
101431	103399	101432	455	700	685	325	585	225	350
101470	101472	101471	430	650	650	295	545	150	325
101608	101610	101609	405	650	635	300	540	150	325

Note: L1 is measured from the lower edge of the mudguard to the centre of the bracket.



1.4 WHITE LINE 1/4 SUPRA






Parlok White Line™ 1/4 mudguard is a cost effective solution for all requests of light and durable mudguard mounting. A wide range of lengths and widths can be provided to enable a unique and cost-efficient appearance.

WITH S42 & P42 BRACKETS





The assembly of the 1/4 mudguard is very easy with the brackets S42 and P42 that secure the quarter mudguard tightly on the tube stay preventing it from spinning. The range of adjustment is 86 mm for P42 and 65 mm for S42.

WL ¼ SUPRA	WITH S42	WITH P42	В	L	R	s	н	F	B1	L1
102302	103363	103212	720	1100	630	345	565	400	450	350
102219	103362	103211	680	1100	630	345	565	400	350	350
102158	103360	102161	650	1050	630	305	540	400	350	325
102012	103358	102013	600	950	580	325	520	300	335	325
101961	103357	101964	550	950	550	340	505	300	225	325
101934	103356	101935	500	950	500	360	480	300	225	325
101866	103355	101867	455	1100	685	325	585	400	150	325
101805	103354	101806	430	1050	650	295	545	400	150	325
102146	103359	103209	405	1050	635	300	540	400	150	325

Note: L1 is measured from the lower edge of the mudguard to the centre of the bracket.



1.5 BLACK LINE



The Parlok Black Line™ mudguard is a full black version of the original mudguard with two white lines. The Black Line mudguards, too, are made of PE-HD (high density polyethylene) and they have a large range of usage temperature and excellent chemical resistance. They are strong against wear & tear and light in weight. A wide range of lengths and widths can be made to various requirements.

BLACK LINE SMALL RADIUS



These three sizes with widths 240, 270 and 320 mm are suitable for small single wheels in commercial vehicles.

В	L	R	s	н
680	1900	630	1260	590
650	1800	580	1160	570
595	1700	550	1100	535
550	1700	550	1100	535
500	1700	550	1100	535
480	1800	580	1160	570
455	1600	510	1020	510
430	1900	650	1290	580
405	1900	635	1265	595
320	1640	540	1075	490
270	1500	480	960	480
240	1300	420	840	410
	680 650 595 550 500 480 455 430 405 320 270	680 1900 650 1800 595 1700 550 1700 500 1700 480 1800 455 1600 430 1900 405 1900 320 1640 270 1500	680 1900 630 650 1800 580 595 1700 550 550 1700 550 500 1700 550 480 1800 580 455 1600 510 430 1900 650 405 1900 635 320 1640 540 270 1500 480	680 1900 630 1260 650 1800 580 1160 595 1700 550 1100 550 1700 550 1100 500 1700 550 1100 480 1800 580 1160 455 1600 510 1020 430 1900 650 1290 405 1900 635 1265 320 1640 540 1075 270 1500 480 960


The above list includes the standard sizes for the Black Line. Please note, however, that all White Line products can be delivered also as Black Line, with or without brackets and spray-suppression. For further information please contact our Sales Team.



1.6 STEERING AXLE MUDGUARDS

STEERING AXLE MUDGUARDS F150






Parlok White Line™ steering axle mudguards for a large span requirement. The range covers all usual lengths and widths of mudguards for the wheel sizes on steering axle. Available also with integrated spraysuppression.

The mudguard is stretched by F1 mm to achieve the Span (S) = $2 \times \text{Radius}$ (R) + F1.

ITEM NO.	В	L	R	S	н	F1
101204	670	2300	670	1490	670	150
101200	550	1850	550	1250	530	150
101190	480	1950	580	1310	580	150
101179	430	2050	650	1450	580	150

STEERING AXLE SUPRA F150






Parlok White Line™ Supra steering axle mudguards for a large span requirement and with integrated spray-suppression. Available in various lengths and widths covering all common wheel sizes on steering axle.

The mudguard is stretched by F1 mm to achieve the Span (S) = $2 \times \text{Radius}$ (R) + F1.

ITEM NO.	В	L	R	s	н	F	F1
101720	670	2700	670	1490	1070	400	150
101718	550	2150	550	1250	930	300	150
101711	480	2250	580	1310	980	300	150
101698	430	2450	650	1450	980	400	150

STEERING AXLE MUDGUARDS F400






Parlok White Line™ steering axle F400 mudguards are designed for the wheel's extra manoeuvring space and a large span requirement. They are made of three parts ie. 2 x round + 1 x straight piece by welding them together and securing the joints with rivets on the side. The length of the straight part is 400 mm. The range covers all usual lengths and widths for the wheel sizes on steering axle. Available also with integrated spray-suppression.

ITEM NO.	В	L	R	S	н
102669	680	2500	630	1660	690
102668	480	2340	580	1570	630
102666	430	2560	650	1700	705

STEERING AXLE SUPRA F400





Parlok White Line™ steering axle mudguards for the wheel's extra manoeuvring space, with integrated spray-suppression. The length of the straight part is 400 mm.

ITEM NO.	В	L	R	S	н	F
102743	680	2900	630	1660	1090	400
102742	480	2640	580	1570	930	300
102739	430	2960	650	1700	1105	400

1.7 TANDEM / TRIDEM MUDGUARDS

WLTANDEM



Parlok White Line™ Tandem mudguards are provided in two widths (430 mm and 650 mm) and a wide selection of lengths. Multiple assembly options are enabled through consistent customer oriented solution searching. You can also assemble the mudguard from straight and curved sections. The strengthening hollows ensure even a long mudguard staying in shape and give support to the construction. An integrated spray-suppression system is also available as an option.

WL TANDEM SUPRA



Parlok White Line™ Tandem mudguards with integrated Supra spray-suppression are provided in two widths and in a wide range of lengths. Multiple assembly possibilities are enabled through consistent customer oriented solution searching. The strengthening hollows ensure even a long mudguard staying in shape and give support to the construction.


WLTANDEM

ITEM NO.	В	L	R	s	н
102732	650	3480	650	2680	680
102696	430	3480	650	2680	680


WL TANDEM SUPRA


ITEM NO.	В	ı.	R	s	н	F
102764	650	3880	630	2680	1080	400
103213	430	3880	650	2680	1080	400

TANDEM AND TRIDEM PARTS AND ASSEMBLY



Parlok White Line™ Tandem and Tridem mudguards can be delivered also in sections, which saves space in transportation. This way you can use the straight and curved parts and assemble the mudguard by yourself. The curved part is available also including Supra spray-suppression.





ITEM NO.	В	L	R	s	н	F
102690	430	2070*	650	1650	705	
102682	430	1000		1000		
102688	430	1380		1380		
103217	430	1450	650		1080	400

^{*}Length without the joint piece of the straight part

ITEM NO.	В	L	R	s	н	F
102726	650	2050*	630	1630	695	
102724	650	1000		1000		
102725	650	1420		1420		
102761	650	1450	630		1095	400

^{*}Length without the joint piece of the straight part

In addition, you need 1 x installation kit per mudguard::

100359 Installation kit for width 430 mudguard straight including 6 pcs M6 screws, nuts and washers


100360 Installation kit for width 650 mudguard straight including 8 pcs M6 screws, nuts and washers



1.8 WHITE LINE 3-PIECE MUDGUARDS

WHITE LINE 3-PIECE MUDGUARDS






Parlok White Line™ 3-piece mudguard set is specifically designed for use in narrow installation environments. Every component has been carefully engineered to ensure optimal functionality right down to the smallest detail. The structure is designed to make the end-user's work easier without compromising on visual appeal. The upper section of the mudguard can be easily removed and replaced when needed.

WHITE LINE 3-PIECE MUDGUARDS SUPRA





Parlok White Line™ 3-piece mudguard set is available also with integrated Supra spray-suppression. The upper section of the mudguard is easy to remove and replace if necessary.

WHITE LINE 3-PIECE MUDGUARDS


ITEM NO.	В	L	R	s	н
100943	680	1900	630	1260	590
100982	670	2090	670	1340	660
101038	650	1900	630	1260	590
101412	480	1800	580	1160	570
101678	430	1900	650	1290	580
101679	405	1900	635	1265	595

WHITE LINE 3-PIECE MUDGUARDS SUPRA

ITEM NO.	В	L	R	s	н	F
101691	680	2200	630	1260	890	300
103207	670	2390	670	1340	960	300
101688	650	2200	630	1260	890	300
103208	480	2100	580	1160	870	300
102195	430	2200	650	1290	880	300
102196	405	2200	635	1270	890	300

1.9 COLOUR LINE






Parlok White Line™ mudguards are available also in colour providing a further option for a bodybuilder and his customer to design a vehicle and its appearance.

We offer our whole range with mudguards including brackets, Supra spray-suppression etc. also in colour. The standard colours are:

Blue RAL 5010 Red RAL 3000 White RAL 9003 Green RAL 6018 Yellow RAL 1018 Silver RAL 9022

Other colours according to your wish are also available.

For further information please contact our Sales Team.



In addition to standard White Line and Black Line versions, you can choose a custom Colour Line, tailored to your brand colours or design. The Colour Line offers a virtually unlimited range of colour combinations.

ITEM NO.	В	L	R	s	н	COLOUR
100934	680	2175	630	1260	730	Red
100892	680	1900	630	1260	590	Red
100891	680	1900	630	1260	590	Blue
100870	680	1900	630	1260	590	White
100883	680	1900	630	1260	590	Green
100876	680	1900	630	1260	590	Yellow
101061	650	1900	630	1260	590	Red
101057	650	1900	630	1260	590	Blue
101070	650	1900	630	1260	590	White
101054	650	1900	630	1260	590	Green
101051	650	1800	580	1160	580	White
101117	630	1850	580	1160	595	Red
101116	630	1850	580	1160	595	Blue
103406	630	1850	580	1160	595	White
101113	630	1850	580	1160	595	Green
101104	630	1650	580	1150	495	Red
101099	630	1650	580	1150	495	Blue
101096	630	1650	580	1150	495	White
101100	630	1650	580	1150	495	Green
101245	595	1700	550	1100	530	Red
101244	595	1700	550	1100	530	Blue
101227	595	1700	550	1100	530	White
101240	595	1700	550	1100	530	Green
101398	480	1800	580	1160	580	Red
101396	480	1800	580	1160	580	Blue
101388	480	1800	580	1160	580	White
101394	480	1800	580	1160	580	Green
101496	430	1900	650	1300	580	Red
101487	430	1900	650	1300	580	Blue
101524	430	1900	650	1300	580	White
101489	430	1900	650	1300	580	Green
101637	405	1900	635	1270	595	Red
101626	405	1900	635	1270	595	White
101630	405	1900	635	1270	595	Green
101334	405	1800	580	1270	595	Red

Note: The above listed colour variants represent only a selection. All mudguards can be supplied in colour. Contact our Sales Team for details.

1.10 FLAT TOP



Parlok Flat Top mudguards are available in a wide range of sizes, suitable for various demands. This type of mudguard is used in, for example, delivery trucks.

The premium material guarantees both outstanding durability and an attractive finish. Reinforcement hollows on the top provide structural strength and ensure a sleek shape. The mudguard can be mounted easily and cost-effectively.


ITEM NO.	В	L	R	s	н	F
100256	550	1880	570	1150	570	545
100248	510	1770	530	1050	570	530
100271	450	1570	470	950	490	440
100264	450	1400	420	840	440	330
100287	260	1570	460	925	480	475
100298	260	1400	430	860	440	370



1.11 SPAT

STRAIGHT SPAT






The straight SPAT is very easy to fasten with just screws through the top to a vehicle's plywood bottom plate, for example. No additional support is required. The compatibility especially in the sizes 450x640 mm and 450x730 mm to commonly used spat & valance systems in semi-trailers is a great advantage in the after sales business. The products can also be equipped with Supra spray-suppression.

ITEM NO.	В	s	н	A
104570	720	178	670	150
104659	680	178	670	150
104868	600	180	610	150
104804	450	141	400	122
104805	450	153	640	122
104806	450	153	730	122
104803	260	121	400	102

CURVED SPAT





Parlok provides a wide range of SPAT mudguards, suitable for various needs. The curved SPAT is very easy to fasten with just screws though the top. No additional support is needed. Parlok 460 Spat is most commonly used in a Spat + Valance mudguard construction for a single tyre.

ITEM NO.	В	S	н
100260	460	180	600
104597	460	180	400

[1.12 SUPRA SPAT + VALANCE



ITEM NO.	В	н	A	F	L
101889	460	600	120	400	900
102746		140			4000



1.13 MUDFLAPS

MUDFLAPS PE



ITEM NO.	В	н
100705	720	400
100557	650-680	400
100600	595-630	400
100541	550	300
100660	480-500	300
100593	450-455	400
100510	405-430	400


The Parlok mudflap range is designed for the use on mudguards and in the rear of the vehicle for protecting other traffic from waterspray formed by the tyre contact to wet road surface. Products are 100% recyclable with excellent weather and chemical resistance and they are strong against wear and tear. Option for logo and other print. White mudflaps are also available upon request.

ANTI-SPRAY SUPRA PE



ITEM NO.	В	B1	B2	L1	L2
100831	720	720	685	400	820
100818	650-680	650	615	400	820
100812	595-630	600	560	400	820
100803	550	550	515	300	720
100795	480-500	480	445	300	720
100793	450-455	450	420	400	820
100780	405-430	405	370	400	820

Parlok Supra™ spray-suppression mudflap is manufactured of high-density polyethylene (PE-HD). It can be supplied either integrated into a mudguard or as a separate component, as it is easy to install afterwards. If shortening of the Supra mudflap is required, it can be done in full 100 mm sections.



MUDFLAPS TPE





TPE mudflaps are made of thermoplastic elastomer, a material known for its elasticity and exceptional impact strength. The flaps are easily and securely attached using a 13 mm or 15 mm bulging profile. Please ask for more information. Option for logo and other print.

ITEM NO.	В	н
103280	650	260
100773	650	350
103282	650	400
103277	600	260
103278	600	350
103279	600	400
103274	550	260
104869	550	350
100752	550	400
103272	400	260
100727	400	350
103273	400	400
103269	200	260
103270	200	350
103271	200	400

The above list outlines the sizes and item numbers for the plain TPE mudflaps without a bulging profile.

REAR FLAPS TPE



Elastic rear flap, made of thermopastic elastomer (TPE), is engineered to be attached to the underrun bar in the rear of the vehicle for protecting other traffic from waterspray and debris generated by the vehicle. Option for logo and other print. The rear flap is carried by a round bulge that slides into a profiled groove.



[COMMERCIAL VEHICLES]

2 INSTALLATION PARTS

PRODUCT RANGE

Parlok can offer you a wide range of various solutions for mounting the mudguards, starting from tube stays and extending to the always suitable mounting bracket option based on customer requests. This way the customer can rely on Parlok as a supplier of a whole variety of accessory.

Parlok products fulfill the official requirements but in addition our products go through testing at our own premises as well. The durability of the brackets used in Parlok mudguards is tested regularly in our own testing facilities. The vibration test simulates the stress experienced by the brackets and their fastenings due to uneven road conditions. The vibration frequency is adjusted until the mudguard resonates and vibrates as much as possible.



Brackets

Brackets can be ordered as pre-installed on the mudguards or separately if you prefer your own assembly. The product range covers different bracket types that can be installed either through slots or a drill pattern of your choice. All our brackets offer a wide adjustment range, making it very easy to install them on the vehicle.

Tube stays and bushings

Tube stays are available as black powder-coated or zinc-coated, or even as stainless steel for a more demanding environment. If you can't find the option you are looking for in the product range please ask our Sales Team. We also deliver bushings for all the tube stay versions.

- + Brackets: S42 & P42 (installation using slots) MR & VRX (installation using a drillpattern) Flat brackets
- + Tube stays: Black powder-coated Zinc-coated Stainless steel
- + Bushings: Weld-on Screw-on



We produce virtually no waste nor emissions and our products are completely recyclable.

2.1 BRACKETS

BRACKET S42






PRODUCT	FOR TUBE Ø	ADJUSTMENT RANGE
100409 S42 in parts	42 mm	65 mm
104445 S42 single-packed	42 mm	65 mm
100402 Wedge piece	34 mm	65 mm
100403 Wedge piece	38 mm	65 mm
100404 Wedge piece	40 mm	65 mm

S42 - THE LIGHTER VERSION

- + Made of strong technical plastics PA6/PE-HD
- + Perfectly suitable to demanding conditions
- + Very light and free of corrosion
- + Wide range of adjustment 65 mm
- + Option to customise the bracket position
- + Unlimited range to fit the mudguard on vehicle
- + Very easy assembly with just one nut to tighten per bracket
- + Available even for the support tubes with diameter 40, 38 and 43 mm with an adapter piece
- + Max. tightening torque 10Nm
- + Interchangeable with P42 bracket
- + Item No. 100409 Bracket S42 in parts
- + Item No. 104445 Bracket S42 singlepacked



BRACKET P42






Weight 0,36 kg

PRODUCT	FOR TUBE Ø	ADJUSTMENT RANGE
100413 P42 in parts	42 mm	86 mm
100414 P42 single-packed	42 mm	86 mm
100402 Wedge piece	34 mm	86 mm
100403 Wedge piece	38 mm	86 mm
100404 Wedge piece	40 mm	86 mm

THE ORIGINAL PARLOK BRACKET


- + Made of zinc coated steel, with a highgrade electrochemical zinc-nickel plated clamp
- + Perfectly suitable to demanding conditions
- + Wide range of adjustment 86 mm
- + Option to customise the bracket position
- + Unlimited range to fit the mudguard on vehicle
- + Very easy assembly with just one nut to tighten per bracket
- + Available even for the support tubes with diameter 40, 38 and 34 mm with an adapter piece
- + Max tightening torque 20Nm
- + Interchangeable with S42 bracket
- + Item No. 100413 Bracket P42 in parts
- + Item No. 100414 Bracket P42 singlepacked



BRACKET MR



The MR adjustable plastic bracket is made of strong highquality technical plastic (PA6), highly durable in all road conditions.



ADJUSTABLE PLASTIC BRACKET


- + Range of adjustment 150 mm
- + Distance between mounting holes 310 mm
- + MR42 suitable for Ø42, with inserts for Ø40, Ø38, Ø34 mm support tubes
- + MR50 suitable for Ø51, with inserts for Ø48, Ø46, Ø44 mm support tubes
- + Aerodynamical design
- + Easy to adjust and open, practical hinge
- + Stable and firm
- + Easy to slide on tube stays
- + Doesn't rust and is chemical resistant
- + Screw and nuts with Geomet surface treatment
- + Max. tightening torque 10 Nm

ITEM NO.	PRODUCT	ADJUSTMENT RANGE	LENGTH	TUBE Ø	FOR MUDGUARD R
100422	MR 42	150	305	42	500-700
100422+100404	MR 40	150	305	40	500-700
1004222100403	MR 38	150	305	38	500-700
100422+100402	MR 34	150	305	34	500-700
100426	MR 51	150	305	51	500-700
100426+100404	MR 48	150	305	48	500-700
100426+100403	MR 46	150	305	46	500-700
100426+100402	MR 44	150	305	44	500-700

BRACKET VRX



Adjustable steel bracket is a proven traditional mudguard mounting bracket. It is available as plain zinc coated steel or with a black coating. We can even provide a stainless steel version upon request. Range of adjustment 150 mm.



ADJUSTABLE STEEL BRACKET

- + Proven traditional mudguard mounting bracket
- + Available as plain zinc coated steel, with a black coating or as a stainless steel version
- + Range of adjustment 150 mm
- + Max. tightening torque 10 Nm
- + Item No. 103045 Bracket VRX42 Zn
- + Item No. 103048 Bracket VRX42 stainless steel
- + Item No. 103051 Bracket VRX42 black

FLAT BRACKETS



The flat brackets are made of 8 mm Strenx® 650 MC hot-rolled high-strength structural steel (HSS), and the surface treatment is hot-dip galvanising (70 µm).


ROBUST FLAT BRACKET

- + Width 60 mm
- + Available length: 500, 540, 600 mm
- + Mounting arm bottom plate thickness 10 mm for improved durability
- + Mounting arm length: 110, 140, 180 mm
- + Shaped additional support fits all bracket lengths: Item No. 104291
- + Fixing holes aligned to various lengths
- + Separate installation kit: Item No. 103915







ITEM NO.	PRODUCT
104286	Flat bracket 500 mm
104287	Flat bracket 540 mm
104288	Flat bracket 600 mm
104283	Flat bracket mounting arm 110 mm
104285	Flat bracket mounting arm 140 mm
104284	Flat bracket mounting arm 180 mm
104291	Flat bracket support, HDG
103915	Installation kit for the flat bracket arm
103909	Installation kit for for the flat bracket




FLAT BRACKETS






Flat bracket mounting arm 110 mm. Bottom plate thickness 10 mm.





Flat bracket mounting arm 140 mm. Bottom plate thickness 10 mm..





Flat bracket mounting arm 180 mm. Bottom plate thickness 10 mm.

ROTATING FLAT BRACKETS

ITEM NO.	PRODUCT
150458	Rotating flat bracket 620x60x6 mm HDG
150489	Rotating flat bracket 580x60x6 mm HDG
150459	Upper support for rotating flat bracket 230x60x6 mm HDG



2.2 TUBE STAYS AND BUSHINGS



Parlok can offer you a wide range of various solutions for mounting the mudguards, starting from tube stays and extending to the always suitable mounting bracket option based on customer requests. This way the customer can rely on Parlok as a supplier of a whole variety of accessory.

Our product range of tube stays consists of black powder-coated stays in many versions: with or without flange, with an M16 or an M14 screw, straight or with offset. The zinc-coated versions are available even with a double-bend or a 3-screw attachment, which ever is more suitable for your needs. Also tube stays in stainless steel are included in our product range.


We deliver bushings for all the tube stay versions.

Note! All tube stays are delivered with the end plug but please note that the locknuts and washers must be ordered separately with their own item numbers:

100203 Locknut Nyloc M16 DIN985/8 Zn / 100205 Locknut Nyloc M14 DIN985/8 Zn 100226 Washer M16 ISO 7089 HV200 Zn / 100228 Washer M14 ISO 7089 HV200 Zn

TUBE STAYS POWDER-COATED WITH FLANGE, M16 / M14






We can provide you a wide range of powder-coated tube stays with diameter 42 mm for various mounting conditions. Tube stays are made of steel and they are black polyester powder-coated. Pretreatment is made with ecological zirconium process. The tube stays are available with an M16, some even with an M14 screw.

ITEM NO.	A	В	С	D	E	BENDS	SCREW
100334	700	536	100	42	31	Single	M16
100316	540	376	100	42	31	Single	M16
100346	700	536	50	42	31	Single	M16
100400	554	390	50	42	31	Single	M16
100350	780			42	31	None	M16
100331	700			42	31	None	M16
100323	540			42	31	None	M16
100341	740	580	100	42	56	Single	M14

TUBE STAYS ZINC-COATED WITH FLANGE, M16 / M14






Zinc-coated tube stays are an excellent choice to demanding conditions. They are available as straight tubes or tubes with an offset.

Some of the zinc-coated tube stays are available also with an M14 screw.

ITEM NO.	A	В	С	D	E	BENDS	SCREW
104259	540			42	31	None	M16
104271	540	376	50	42	31	Single	M16
100318	540	376	100	42	31	Single	M16
104344	635	392	50	42	31	Double	M16
104261	700			42	31	None	M16
104272	700	536	50	42	31	Single	M16
104263	700	536	100	42	31	Single	M16
104435	705	485	50	42	56	Double	M16
104434	760	485	150	42	56	Double	M16
104433	760	485	100	42	56	Double	M16
100351	780	620	100	42	46	Single	M14
100344	740	580	100	42	46	Single	M14
							40

TUBE STAYS WITHOUT FLANGE







Powder-coated or Zn tube stays with diameter 42 mm, without flange, are suitable for various mounting conditions.

ITEM NO.	A	В	С	D	COLOUR	BENDS
103696	750			42	Zn	None
103697	650			42	Zn	None
100387	760	465	150	42	black	Double
100376	760	485	150	42	Zn	Double
103703	760	480	100	42	Zn	Double
100388	760	480	50	42	black	Double
100375	705	460	50	42	Zn	Double

STAINLESS STEEL TUBES








ITEM NO.	A	В	С	D	BENDS
103701	705	485	50	42	Double
103704	760	485	150	42	Double

TUBE STAYS WITH FLANGE AND SCREW ATTACHMENT



The C-Profile bracket set (100366) is our own innovation popular already for a long time through its' low cost. C-profile is made of zinc-coated steel and is available as a 3-bolt mounting variation. It is especially suitable for narrow installation conditions. The set is delivered inclusive the end plug and installation kit. The installation kit is available also separately with item number 100368.

BUSHINGS



There is a suitable bushing to all tube stays. You can choose between weld-on or screw-on bushings to find the option that best suits your vehicle.



[COMMERCIAL VEHICLES] 3 TOOLBOXES

PRODUCT RANGE

Parlok toolboxes are produced of high quality polyethylene (PE-HD) that is a 100% recyclable material. The boxes are very light in weight with easy and quick assembly. A wide range of sizes is available. You can secure the contents as the boxes are lockable with an additional option for a padlock.

Due to the material PE-HD the toolboxes have a high impact resistance and in addition they are

very temperature and chemical resistant. They are corrosion free, which means they don't need painting, they will not rust.

Toolboxes are delivered as standard without brackets. The installation kit can, however, be ordered with a separate item number.

Installation kit is available for both vertical and horizontal installation.



Further options

The standard colour for the Parlok toolboxes is black but you can customise your vehicle and order sizes 700L and 800 also in red or military green.



Toolbox bogie is a popular and useful innovation that enables efficient usage in a limited space.

For the storage of lashing straps, we offer a size 700 box, which provides storage space for up to eight lashing straps.

Fire extinguisher boxes


The toolbox product range includes also fire estinguisher boxes that are available in two sizes. The fire extinguisher boxes are made of thermoplastic elastomer TPE.

- + Produced of strong and durable high-density polyethylene
- + 100% recyclable material
- + Modern design and light in weight
- + Easy to install
- + Wide range to choose from
- + Lockable (additional option for a padlock)
- + High impact resistance
- + Temperature and chemical resistant
- + Will not rust (no painting needed)
- + Delivered as standard without installation kit
- + Installation kit available with a separate item number
- + Approved as lateral protection according to Council Regulation No. 73. Approval mark E1 73R - 010075



We produce virtually no waste nor emissions and our products are completely recyclable.

3 TOOLBOXES



550 SL



ITEM NO.	PRODUCT	w	н	D
100451	Toolbox 550 SL	550	450	450

Max. load 50 kg

Installation kit available with a separate item number: 102812 Installation kit for toolbox 550 SL2 horizontal 102827 Installation kit for toolbox 550 SL4 vertical

600 SL



ITEM NO.	PRODUCT	w	н	D
100452	Toolbox 600 SL	600	450	450

Max. load 50 kg

Installation kit available with a separate item number: 102901 Installation kit for toolbox 600 SL2 horizontal 102902 Installation kit for toolbox 600 SL4 vertical

Installation kit is not automatically included with the delivery. Please order using the separate item number.

700 SL



ITEM NO.	PRODUCT	w	н	D
100454	Toolbox 700 SL	700	450	450

Max. load 100 kg

Installation kit available with a separate item number: 102864 Installation kit for toolbox 700 SL2 horizontal 102863 Installation kit for toolbox 700 SL4 vertical

700L SL



ITEM NO.	PRODUCT	w	н	D
100453	Toolbox 700L SL	700	300	300

Max. load 30 kg

Installation kit available with a separate item number: 102812 Installation kit for toolbox 700L SL2 horizontal 102827 Installation kit for toolbox 700L SL4 vertical

800 SL



ITEM NO.	PRODUCT	w	н	D
100455	Toolbox 800 SL	840	480	485
100456	Toolbox 800T SL	840	480	550

Max. load 100 kg

Installation kit available with a separate item number: 102867 Installation kit for toolbox 800 SL2 horizontal 102866 Installation kit for toolbox 800 SL4 vertical

1000 SL



ITEM NO.	PRODUCT	w	н	D
100450	Toolbox 1000 SL	1000	500	460
100458	Toolbox 1000D SL	1000	500	640

Max. load 100 kg


Installation kit available with a separate item number: 102809 Installation kit for toolbox 1000 SL2 horizontal 102808 Installation kit for toolbox 1000 SL4 vertical

Installation kit is not automatically included with the delivery. Please order using the separate item number.

3 TOOLBOXES

700 MK1





+ An innovation that enables the efficient usage in a limited space.


ITEM NO.	PRODUCT	w	H D 420 620	
100448	Toolbox 700 bogie	700	420	620

Installation kit available with a separate item number: 104762 Installation kit for toolbox 700 bogie

LASHING STRAP BOX








- + Holds up to 8 lashing straps + Watertight HD-PRE box
- + The box can be locked to secure the contents
- + Delivered complete with mounting straps

ITEM NO.	PRODUCT	w	н	D
100449	Lashing strap box	700	500	450

TPE 6 FIRE EXTINGUISHER BOX





- + Material: TPE
- + Weather resistant -20°C
- + 3 hinges, 2 quick release fasteners
- + Fixing belt for the extinguisher
- + Sealing eyelets
- + Polycarbonate window

- + Water-proof sealing
- + Right-hand or left-hand opening
- + Weight: 2,10 kg
- + Measurements W x H x T 282 x 635 x 233 mm

ITEM NO.	w	н	D
100440	282	635	233

TPE 9 FIRE EXTINGUISHER BOX



320

- + Material: TPE
- + Weather resistant -20°C
- + 3 hinges, 2 quick release fasteners
- + Fixing belt for the extinguisher
- + Sealing eyelets

- + Polycarbonate window
- + Water-proof sealing
- + Right-hand or left-hand opening
- + Weight: 4,15 kg
- + Measurements W x H x T 320 x 786 x 230 mm

ITEM NO.	w	н	D
100441	320	786	230



[COMMERCIAL VEHICLES] 4 AERO PANELS

AERO PANELS FOR SIDEGUARD SYSTEMS

The Parlok concept as a whole represents a sustainable solution for the commercial vehicle sector. Parlok aerodynamic sideguard system with a fastening kit saves hundreds of litres of fuel and contributes to reducing CO2 emissions with tons per year. It is a responsible choice for the future.

The Parlok Aero panels for sideguard system's function is to reduce the turbulence under and drag behind the trailer by directing the airflow more economically past the trailer. According to CFD simulations and track tests the Parlok sideguard comes up to 13% in drag reduction and over 5% in fuel consumption measured for a



combination of towing vehicle with a standard semi-trailer.

Aero in practice

With Parlok Aero panels, an aerodynamic sideguard system can be configured using straight and wheel arch panels, complemented by front and rear deflectors.

Parlok offers a variety of cover plates all contributing in improving the vehicle's aerodynamics and thus resulting in fuel savings as well as reduction of CO2 emssions.

- + Aerodynamic design and elegant appearance
- + The reduction of aerodynamic turbulence and drag up to 13 % and fuel savings up to 5 %
- + Return of investment even in less than one year
- + Strong, lightweight construction
- + Easy to install
- + Easy maintenance and change of components
- + Material polypropylene PP
- + Paintable
- + Can be customised to various lengths



We produce virtually no waste nor emissions and our products are completely recyclable.

4.1 AERO PANEL ASSEMBLY / FRONT




With Parlok Aero panels you can create an aerodynamic sideguard system consisting of straight and wheel arch panels as well as front and rear deflectors.

Aero panels are made of polypropylene PP. The height of the Aero panel is 720 mm while the length can be customised. Standard delivery is in 1600 mm parts that can be combined as needed. Thickness of the Aero panel is 4-4,5 mm. Standard colours are black, silver, red and blue.

ITEM NO.	PRODUCT	w	н
105118	Deflector 720 Aero black	250	720
105120	Deflector 720 Aero silver	250	720
105121	Deflector 720 Aero red	250	720
105142	Deflector 720 Aero blue	250	720



ITEM NO.	PRODUCT	w	н
105149	Cover panel 720x1600 Aero black	1600	720
105151	Cover panel 720x1600 Aero silver	1600	720
105152	Cover panel 720x1600 Aero red	1600	720
105153	Cover panel 720x1600 Aero blue	1600	720



ITEM NO.	PRODUCT	w	н
105154	Cover panel 720x1600 R675 Aero black, front left/rear right	1600	720
105155	Cover panel 720x1600 R675 Aero black, front right/rear left	1600	720
105158	Cover panel 720x1600 R675 Aero silver, front left/rear right	1600	720
105159	Cover panel 720x1600 R675 Aero silver, front right/rear left	1600	720
105160	Cover panel 720x1600 R675 Aero red, front left/rear right	1600	720
105161	Cover panel 720x1600 R675 Aero red, front right/rear left	1600	720
105162	Cover panel 720x1600 R675 Aero blue, front left/rear right	1600	720
105163	Cover panel 720x1600 R675 Aero blue, front right/rear left	1600	720

4.2 AERO PANEL ASSEMBLY / REAR






Like parts for the front assembly, all parts for the rear assembly are available also in colour: black, silver, red and blue.

ITEM NO.	PRODUCT	w	н
105155	Cover panel 720x1600 R675 Aero black, front right/rear left	1600	720
105154	Cover panel 720x1600 R675 Aero black, front left/rear right	1600	720
105159	Cover panel 720x1600 R675 Aero silver, front right/rear left	1600	720
105158	Cover panel 720x1600 R675 Aero silver, front left/rear right	1600	720
105161	Cover panel 720x1600 R675 Aero red, front right/rear left	1600	720
105160	Cover panel 720x1600 R675 Aero red, front left/rear right	1600	720
105163	Cover panel 720x1600 R675 Aero blue, front right/rear left	1600	720
105162	Cover panel 720x1600 R675 Aero blue, front left/rear right	1600	720

ITEM NO.	PRODUCT	w	н
105164	Cover panel 720x1600 Aero black, rear left	1600	720
105165	Cover panel 720x1600 Aero black, rear right	1600	720
105168	Cover panel 720x1600 Aero silver, rear left	1600	720
105169	Cover panel 720x1600 Aero silver, rear right	1600	720
105170	Cover panel 720x1600 Aero red, rear left	1600	720
105171	Cover panel 720x1600 Aero red, rear right	1600	720
105172	Cover panel 720x1600 Aero blue, rear left	1600	720
105173	Cover panel 720x1600 Aero blue, rear right	1600	720

4.3 AERO BRACKETS



The brackets are designed for easy fitting of Aero panels and deflectors on a vehicle providing the strength of the lateral protection device. A smart locking mechanism allows an easy opening or lifting off of the panels when access to the underside of the chassis is needed. The lightweight but strong-built brackets feature a smart-looking and reliable locking mechanism. Attachment can be adjusted according to the bar distance.


ITEM NO.	PRODUCT
105135	Sideguard installation bracket foldable retrofit
105176	A set of three brackets

Openable bracket mounting onto excisting aluminium side rails with two rail screws (M8x20). The outer bracket to be mounted onto the inside of the Aero panel.




ITEM NO.	PRODUCT
105309	Sideguard installation bracket fixed retrofit

Fixed bracket, mounting onto excisting aluminium rails.



4.4 COVER PANELS







Parlok cover panels contribute in improving the vehicle's aerodynamics thus resulting in fuel savings as well as reduction of CO2 emssions.

The material of the cover panel is polypropylene PP, thickness is 3 mm. Measurements are 500 x 1600 mm. Available in black, silver, red and blue. The panel is attached to the upper and lower edges of the aluminum planks of the chassis by, for example, rivets or screws, with 200 mm fastening intervals. The lower and upper edges of the cover panel are folded 90 degrees.

ITEM NO.	PRODUCT	w	н
105110	Cover panel 500x1600 black	1600	500
105112	Cover panel 500x1600 silver	1600	500
105113	Cover panel 500x1600 red	1600	500
105140	Cover panel 500x1600 blue	1600	500







[5 AGRI & INDUSTRIAL EQUIPMENT]

5 OFF-RD

OFF-RD MUDGUARDS

The primary function of mudguards is to protect the trailer and its load from mud, stones and other debris reducing the risk of damage and maintaining cleanliness. This protection is particularly crucial in agricultural environment, where trailers frequently operate on a muddy and an uneven terrain.

By minimizing the amount of debris thrown onto the road or field, mudguards play a vital role in enhancing the safety of the trailer and other vehicles or machinery operating nearby. They help in maintaining clear visibility and preventing accidents caused by debris-related hazards.

Parlok OFF-RD™ mudguards are designed for demanding use in various agricultural and industrial vehicles and construction machines. There is a wide range of mudguards available with various sizes to choose from.



The OFF-RD product range covers mudguards suitable for tractors, agri trailers, backhoes, telescopic handlers, wheel loaders - you name it.

Customer-specific OFF-RD

Parlok OFF-RD™ custom mudguards are available to all manufacturers of agricultural and industrial vehicles. Thanks to our very flexible production methods we are able to deliver also OFF-RD according to customer specifications.

Our experience of manufacturing millions of mudguards enables us to guarantee a toughmade, purpose-built mudguard in the form you wish to have.

- + Made of high-density polyethylene (PE-HD) with usage temperature -50°C - +80°C
- + 3,5 mm material gives outstanding resistance against wear and tear in extremely demanding conditions
- + Excellent chemical resistance
- + Stylish whole black appearance with Parlok carbon-look surface
- + Wide range of customer-specific solutions
- + Long life cycle and 100% recyclable
- + 50 mm side height for easy installation and more clearance from the tyre




We produce virtually no waste nor emissions and our products are completely recyclable.





5.1 OFF-RD FRONT MUDGUARDS





The original Parlok OFF-RD™ mudguard. Made of PE-HD (high-density polyethylene) with a large range of usage temperature and excellent chemical resistance. Strong against wear & tear and light in weight. A wide range of lengths, widths, radiuses and taylor-made solutions can be manufactured to various requirements.


For more information please contact our Sales Team.

ITEM NO.	В	L	R	S	н
102663	720	1800	850	1480	855
102661	670	1950	950	1625	955
102656	610	1550	820	1330	825
102648	500	1450	800	1260	805
102646	455	1200	685	1050	690
102645	405	1250	720	1100	725
102644	405	1050	635	935	640



5.2 OFF-RD SHORT MUDGUARDS





Just like for tractors, mudguards 70° are indispensable also for agricultural trailers providing essential protection, enhancing safety and contributing to the longevity and efficiency of the equipment. Selecting the right mudguards tailored to specific needs and environmental conditions, can significantly improve the performance and reliability of agricultural transport operations.


Parlok short mudguards are especially designed to be used on agri trailers. Multiple fastening options are available.

ITEM NO.	В	L	R	S	н
104924	720	980	800	525	755
104920	670	980	800	525	755
104922	670	820	670	440	630
104916	610	900	740	480	695
104918	610	840	685	450	645
104912	550	670	550	360	520
104914	500	840	685	450	645
104908	500	670	550	360	520
104910	455	840	685	450	645
104906	405	780	635	420	600



5.3 OFF-RD LONG MUDGUARDS





The OFF-RD™ mudguards are available also in a long 160° version, specifically designed for agricultural trailors. Like all Parlok mudguards, also this type is made of PE-HD (high-density polyethylene). We offer a wide range of lengths, widths and radiuses, and can produce custommade solutions to meet various requirements.

ITEM NO.	В	L	R	s	н
104925	720	2230	800	1580	750
104921	670	2230	800	1580	750
104923	670	1870	670	1325	630
104917	610	2070	740	1465	695
104919	610	1910	685	1355	645
104913	550	1540	550	1090	520
104915	500	1910	685	1355	645
104909	500	1540	550	1090	520
104911	455	1910	685	1355	645
104907	405	1770	635	1255	595



5.4 OFF-RD CUSTOM MUDGUARDS



Parlok OFF-RD™ custom mudguards are available to all manufacturers of agricultural and industrial vehicles. They can be customer's own design or designed by Parlok engineering and produced in our efficient thermoforming process.

Due to the type of manufacturing process the investment cost is relatively low and especially suitable for annual volumes between 500 to 10.000 pieces.

Thanks to our experience of manufacturing millions of mudguards we are able to guarantee a tough-made, purpose-built mudguard in the form you wish to have.



- + Size up to appr. 950 x 1950 x 600 mm
- + Made of high-density polyethylene (PE-HD) with usage temperature -50°C - +80°C
- + 3,5 mm material gives outstanding resistance against wear and tear in extremely demanding conditions
- + Excellent chemical resistance
- + Stylish whole black appearance with Parlok carbon-look surface
- + Wide range of customer-specific solutions in length, width, radius, drilling and shape
- + Long life cycle and 100% recyclable
- + 50 mm side height for easy installation and more clearance from the tyre



6 CONTRACT MANUFACTURING

Parlok is your reliable partner for contract manufacturing using thermoforming which is a very advantageous way to make accurately shaped, durable lightweight products, especially suitable for annual volumes between 500 to 10.000 pieces, with a mould cost starting at approximately 1000 €.

We manufacture a wide variety of molded plastic products and have extensive experience in assembly work and product design.

Bring us your idea and we make it happen! Please contact our Sales team for further information.

6.1 SHEET PRODUCTS

With a fast and flexible delivery time we manufacture sheet products of various sizes, made of high-density polyethylene PE-HD and polypropylene PP. Sheet products are available in a smooth finish in a variety of colours and sizes.

Width Length **Thickness** < 1400 mm < 3500 2-8 mm

We have advanced CNC milling capabilities that enable us to cut and drill PE-HD and PP sheets with increased ease and precision.





[6.2 VACUUM-FORMING

Parlok is a manufacturer of a broad array of vacuum-molded plastic products, mainly for the automotive and construction industries, but we are also a contract manufacturer for other customers and industries. We have an efficient vacuum-forming department operating in three shifts, and our own sheet production.

The main raw materials are PE-HD (high-density polyethylene) and PP (polypropylene) from our own production but we can offer also other materials e.g. ABS.

The maximum size of the molded product can be up to $1850 \times 850 \times 600$ mm (L x B x H). Our modern industrial robots are capable of high precision milling of parts.


[6.3 ASSEMBLY

With our long experience we are able to manufacture various products that require assembly work. Our state-of-the-art industrial robots enable high-precision milling, cutting and perforation that can be taken advantage of in assembly.

After milling the products are transferred to our assembly cells where we can e.g. screw, rivet or weld together plastic and other parts.

[6.4 DESIGN

Leveraging our extensive design experience with various plastic products, we can cost-effectively collaborate on or fully manage the design of our customers' products. Utilizing SolidWorks 3D CAD software and our modern 3D printer, we facilitate easy visualization of the product design. Additionally, we maintain excellent connections with mold suppliers and designers, ensuring a seamless design and production process.





leading manufacturers of mudguards and spray-suppression systems. We also manufacture a wide range of other plastic products.

OY PARLOK ABProduction and international sales

Sysilahden teollisuusalue 5 FI-21600 PARAINEN +358 2 454 2222 parlok@parlok.fi

WWW.PARLOK.COM